GROUPE SEFMAT
RIPACK®

YOUR PROTECTION
BY EXCELLENCE

RIPACK 2500

THE LIGHEST IN ITS CATEGORY

For regular shrink wrapping needs, the Ripack 2500 is the ideal tool for protecting your pallets. With adjustable power, it will adapt to the thickness of your films.

Compact and light, the Ripack 2500 is equipped with «cold nozzle» technology for unparalleled safety.

With its innovative quick and tool-free igniter change system, benefit from a reliable and robust shrink gun.

These heat tools are used in many sectors such as industry, construction, food, transport / logistics ...

TECHNICAL SPECIFICATIONS

Power	34 to 60 kW
Pressure	1,5 to 3,5 bars
Gas consumption	from 2,2 to 4 kg/h
Length/Height	360/262 mm
Package dimensions	460x330x140 mm
Weight	940 g
Package weight	4880 g
Noise level	< 85 dbA
Energy source	Propane gas or natural gas upon request

Propac S.r.l.
Via Ardeatina, 2479 / Km 22,300
z.i. S.Palomba / 00134 Roma [RM]
T [+39] 06715395 / F [+39] 0671539582

Email: info@propac.it
PEC: propac@cgn.legalmail.it
Fax: 800-969827
Numero Verde: 800-008822

Cod. Univoco (SDI) SUBM70N
P.IVA 02033401007
C.Fiscale 08358350588

CCIAA n° 657941
Iscr. Trib. 5739/88
Cap. soc. € 1.000.000,00 i.v.