

MAX380H115

414 x 345 x H129 mm
16.30 x 13.58 x H5.08 inch

380 x 270 x H115 mm
14.96 x 10.62 x H4.52 inch

36 + 79 mm
1.42 + 3.11 inch

1,86 kg / 4.10 lb

-51 / 90 °C / -59.8 / 194° F

Capacità / Capacity
11.79 lt



Stampaggio: ad iniezione
Process: Injection molding

Materiale / Materials
POLIPROPILENE/POLYPROPYLENE
NYLON (Serrature / Latches)



Shipping & Logistic info

2 pz. per cartone
2 pcs. x carton



4,32 Kg per cartone
9.52 lb gross weight



IP67
RATING


MIL SPECS

DEF STAN 81-41
STANAG 4280
MIL STD 810G

- Guarnizione ermetica / Watertight seal around lid
- Valvola automatica di pressurizzazione
Automatic pressure release valve
- Sistema di impilabilità / Stackable interlocking system
- Resistenza agli urti / Thick body material
- Chiusure di sicurezza a doppio step / Easy to open double throw latches
- Manico morbido ad alta ergonomia / Load tested soft grip handle
- Pareti spesse ANTIURTO / Thick body material
- Punti di fissaggio per varie applicazioni / Extra fixing points
- Cerniera lungo tutto il profilo della valigia / Fully length hinges
- Perni in nylon ANTI corrosione / Nylon pins corrosion free



**SCREEN PRINTING &
CUSTOM LABEL**
SERIGRAFIA &
ETICHETTA CUSTOM



**CUSTOMIZED
FOAM INLAY**
INTERNI IN SPUGNA
FUSTELLATA




**LASER MARKING
OR ENGRAVING**
INCISIONE O
MARCATURA LASER



CUSTOM COLOUR
COLORI CUSTOM


Spugne:



BASE FOAM

1 x 10 mm / 1 x 0.39 inch


+



CUBED FOAM

2 x 33 mm / 2 x 1.30 inch

+



CONVOLUTED FOAM

1 x 35 mm / 1 x 1.38 inch

=



H115

S / HDS