

MAX505H280

555 x 428 x H306 mm
21.85 x 16.85 x 12.04 inch

500 x 350 x H280 mm
19.69 x 13.78 x 11 inch

58 + 222 mm
2.28 + 8.74 inch

4,90 kg / 10.80 lb

-51 / 90 °C / -59.8 / 194° F

Capacità / Capacity
49 lt



Stampaggio: ad iniezione
Process: Injection molding

Materiale / Materials
POLIPROPILENE/POLYPROPYLENE
NYLON (Serrature / Latches)



Shipping & Logistic info

1 pz. per cartone
1 pc. x carton



5,88 Kg per cartone
12.96 lb gross weight



IP67
RATING

MIL SPECS

DEF STAN 81-41
STANAG 4280
MIL STD 810G

ATA300

- Guarnizione ermetica / Watertight seal around lid
- Valvola automatica di pressurizzazione
Automatic pressure release valve
- Sistema di impilabilità / Stackable interlocking system
- Resistenza agli urti / Thick body material
- Chiusure di sicurezza a doppio step / Easy to open double throw latches
- Manico morbido ad alta ergonomia / Load tested soft grip handle
- Pareti spesse ANTIURTO / Thick body material
- Punti di fissaggio per varie applicazioni / Extra fixing points
- Cerniera lungo tutto il profilo della valigia / Fully length hinges
- Perni in nylon ANTI corrosione / Nylon pins corrosion free



**SCREEN PRINTING &
CUSTOM LABEL**
SERIGRAFIA &
ETICHETTA CUSTOM



**CUSTOMIZED
FOAM INLAY**
INTERNI IN SPUGNA
FUSTELLATA




**LASER MARKING
OR ENGRAVING**
INCISIONE O
MARCATURA LASER



CUSTOM COLOUR
COLORI CUSTOM


Spugne:



BASE FOAM

1 x 50 mm / 1 x 1.97 inch


+



CUBED FOAM

3 x 55 mm / 3 x 2.16 inch

+



CONVOLUTED FOAM

1 x 50 mm / 1 x 1.97 inch

=



Trolley:

